



Aegis LIC-SLM Bored Lock

## Features & Benefits

- ANSI/BHMA A156.2 Grade 1 Certified, UL 10(C) 3-hour fire rated, and ADA compliant.
- Large double-sided status indicators display lock status on both sides of the door, improving visibility in high-traffic areas.
- Maintains free egress at all times for occupant safety.
- Supports the use of existing key systems, allowing existing cylinders to stay in place and reducing overall upgrade costs.
- Broad retrofit compatibility: fits into any existing cylindrical lock prep, requiring minimal door prep work to install the lock.
- Available in multiple functions and configurations to meet various institutional requirements.

## Specifications

- **Backset:** 2-3/4" standard
- **Door Thickness:** 1-3/4" standard; others available upon request
- **Door Prep:** Standard 161 prep with through holes
- **Handing:** LH / RH; LH to LHR and RH to RHR are field adjusted
- **Lockbody:** Rigid
- **Latch Bolt:** Stainless Steel, Anti-Pick, 1/2" projection
- **Cylinder:** Schlage® "C" keyway, standard; for other cylinder options, see How-to-Order below
- **Faceplate:** Stainless Steel, 1-1/8" wide, standard; Stainless Steel, 1" wide, optional
- **Escutcheon:** Stainless Steel, 10-3/16" x 3-5/32" x 5/8"
- **Strike:** ASA Strike, 1-1/4" x 4-7/8", standard; T-strike, 1-1/8" x 2-3/4", optional
- **Mounting Screws:** Security TORX® screws for external escutcheon use
- **Keying:** KD standard; KA, MK, GMK, GGMK, and Construction keys are also available upon request

### Aegis LIC-SLM How-to-Order

Trim	SLM: Sentinel
Indicator	[Leave Blank]: Indicator Outside/Indicator Inside / <b>B:</b> No Indicator Outside/No Indicator Inside / <b>BI:</b> Indicator Outside/No Indicator Inside / <b>BO:</b> No Indicator Outside/Indicator Inside
Function (Message)	<b>F75:</b> Passage / <b>F76:</b> Privacy / <b>F84T:</b> Classroom / <b>F86:</b> Storeroom / <b>F110:</b> Classroom Intruder / <b>F115:</b> Faculty Privacy
Lever	<b>S:</b> Sentinel / <b>Q:</b> Quest
Handing	<b>LH:</b> Left Hand / <b>RH:</b> Right Hand
Finish	<b>630:</b> Satin Stainless Steel / <b>622:</b> Flat Black
Cylinder	<b>SC:</b> 6-pin with Schlage "C" keyway, standard / <b>SFIC6:</b> 6-pin small format IC, less core / <b>SFIC7:</b> 7-pin small format IC, less core / <b>IC6:</b> 6-pin small format housing core with Best® "A" keyway / <b>IC7:</b> 7-pin small format housing core with Best "A" keyway / <b>CLFIC:</b> Corbin® large format IC, less core / <b>SLFIC:</b> Schlage large format IC, less core / <b>SALFIC:</b> Sargent® large format IC, less core / <b>YLFIC:</b> Yale® large format IC, less core / <b>HS6:</b> High security 6-pin cylinder with TownSteel "L" keyway / <b>HS7:</b> High security 7-pin IC core with TownSteel "L" keyway / <b>LC*:</b> Less cylinder
Strike	[Leave Blank]: T-Strike / <b>A:</b> ASA Strike

\*If using your own cylinder, please consult factory.

SLM - BO - F84T - S - LH - 630 - SC - A

